Metamark MD-100B

3 Year Calendered Blockout Digital Vinyl



Product Description

Metamark MD-100B offers all the benefits of MD-100, with the additional feature of a grey pigmented adhesive to offer improved opacity, and prevent show-through. The 3 year calendered vinyl is suitable for short to medium term outdoor graphics including advertising, point of sale, and other promotional applications. The 100 micron film gives the product ease of handling onto flat panels, and may also be applied to slightly curved surfaces. The bright white finish offers brilliant colour reproduction on Solvent, Eco Solvent, Latex and UV Printers.

Printing and Handling

- Suitable for use on Solvent, Eco Solvent, Latex and U.V. inkjet printers. Always perform a test print first.
- Ensure that the correct profiles and heater settings are used. Most profiles are available for download from www.metamark.co.uk.
- Ensure that the material has reached room temperature and a relative humidity of 50% before printing.
- Do not handle the face film directly and ensure it is free from dust and static.

Application

- Allow the inks to cure before cutting flush to the print, this is usually 24-48 hours. (Not applicable to Latex prints)
- Apply unstressed, in particular to curves and recesses. It is not suitable for application over rivets or complex recesses.
- Avoid wet application the product has a permanent water-based adhesive
- Not recommended for use on low energy surfaces such as polypropylene. The user should determine suitability of substrate.
- Refer to www.metamark.co.uk for application guidelines.

Overlaminating

- Overlamination is recommended to prevent abrasion and to extend colour fastness.
- Allow the inks to cure before overlaminating, this is usually 24-48 hours.
- Apply the matched Overlaminate. For all other laminates the user should determine suitability.

Face Film

Face Film: Gauge: Tensile Strength Elongation at break

Calendered PVC 100 micron nominal 50N/25mm MD / 48N/25mm TD nom. 180% MD nominal

Adhesive

Type Weight Adhesion to glass 20 mins Adhesion to glass 24 hour Perceived tack Application temperature Service temperature Permanent Grey solvent-free acrylic 18gsm nominal 13N/25mm nominal 20N/25mm nominal Medium +8°C to +60°C -20°C to +100°C

Release Liner

Print Weight Type Plain 140 gsm nominal Clay coated kraft paper

Finishes		
Finishes Available	MD-100B MD-101MB	White Gloss White Matt
Roll Presentation		
Roll sizes and net weights	1370mm x 50m 1600mm x 50m	20kg 23kg
Presentation	Face film outwards, on a 76mm core.	
Durability		
Shelf Life	1 year 3 years. This refers to the unprinted vinyl when installed. Refer to ink manufacturer for durability of the finished product.	
External weathering		
Fire Rating	Self Extinguishing	

Warranty: Metamark (UK) Limited warrants to its customers that graphics produced using Metamark Digital Media will remain in good condition without excessive fading or colour degradation for the specified life time of the ink used, when correctly stored, printed and applied in accordance with procedures outlined in the technical literature. If within the specified years of normal use Metamark DigitalVinyl becomes ineffective for its intended use, then Metamark will provide sufficient material to produce a new replacement marking, and will at its own discretion, contribute an allowance in additional material towards the costs involved in replacing the graphics. In all cases, the converter is held fully responsible for storing, processing and applying the unconverted materials in accordance with Metamark's technical specifications. Metamark (UK) Limited will not be liable for any indirect or consequential loss or damage, and will not provide any allowance against improper usage, application accident, negligence, chemical damage or improper repair. **Please Note:** The above data is given in good faith to provide an indication of the performance of the product. Purchasers should consider the suitability of each product for its intended use and the purchaser assumes all risks in connection with such use. Seller shall not be liable for damages in excess of the purchase price of the product nor for incidental nor consequential loss.

Metamark (UK) Limited

Luneside • New Quay Road • Lancaster • LA1 5QP • Tel +44 (0)1524 387140 • Fax +44 (0)1524 387147
Metamark House • Octimum Business Park • Forsyth Road • Woking • GU21 5SF • Tel +44 (0)1483 571111 • Fax +44 (0)1483 570540

sales@metamark.co.uk www.metamark.co.uk