

LUCOLED BL11



- 5 years warranty
 First 2 years extended warranty
- High efficacy: 158lm/W
- Constant Current Technology
- Narrow white binning

Lucoled Plus BL11 modules offer a high quality and efficient backlit solution for channel letters made from routed full acrylic.


Lucoled Plus BL11 modules are IP65 and can be used without the need for fully potting the acrylic letters. This makes the production process much cleaner and faster. Potting material can also damage LED phosphor and can have a colour shift and reduced life as a result. The BL11 is a fully enclosed module and does not have this disadvantage.

Lucoled Plus BL11 can also be used in very narrow and small traditional channel letters.

SPECIFICATIONS

LUMINOUS INTENSITY DISTRIBUTION


- Dimensions 13x7x7mm
- Warranty 5 years (first 2 years extended)
- Beam angle: 120°
- Can be cut between every unit
- UL, CE and RoHS compliant
- Narrow white binning
- Constant Current Technology
- Operating temperature -25~+60C



	1 LED	Injection Molding Device	DC 12V	IP 65	5 Years
--	----------	--------------------------------	-----------	----------	------------

ltem no	LED colour	СТ (К)	CRI	Power (W/mod)	Flux (lm/mod)	Efficacy (lm/W)	Voltage (DC)	Modules per chain	Modules per carton
BL11-W65	white	6500	>70	0.24	38	158	12	50	8400
BL11-W30	white	3000	>70	0.24	38	158	12	50	8400

DIMENSIONS



POWER SUPPLY CAPACITY 12V SERIES

Item	PP1230	PP1260	PP12100	PP12150	PP12200
Power Output	30W	60W	100W	150W	200W
BL11 modules / power supply	112	225	375	562	750
Maximum 50 modules per chain					

PACKAGING

ltem	Qty (pcs/bag)	Qty (bag / carton)	Total Qty (pcs / carton)	Total weight (kg)	Carton size (LxWxH) in mm
BL11	300	28	8400	12.5	264 x 376 x 272