MetaGuard 'FloorArt'

DécorMark Textured Floor Overlaminate



Product Description

MetaGuard FloorArt is a textured floor overlaminate offering Décor and promotional branding opportunities for short term indoor use. The 100 micron matt embossed film gives a durable protection to graphics, with easy to clean finish. This versatile product can also be applied to wall graphics, for a one product solution. MetaGuard FloorArt has an anti-slip finish tested to DIN 51130:2014, achieving an R9 rating. The recommended matched media is Metamark MDPH or MDPHB. Suitable printable with Solvent, Eco Solvent, UV and Latex prints.

Material Handling

- Ensure that the material has reached room temperature and a relative humidity of 50% before printing.
- Do not handle the face film directly and ensure it is free from dust and static.

Printing Guidelines

- The recommended matched print media's for Metamark MDPH or MDPHB.
- Suitable for use on Solvent, Eco Solvent inkjet, UV and Latex prints on Metamark print media.
- Ensure that the correct profiles and heater settings are used. Most profiles are available for download from www.metamark.co.uk.
- Allow 24-48 hours after printing for the ink to gain abrasion resistance.

Application and Care of Floor Graphics

- Apply floor graphics using a dry application method, to smooth, flat, sealed surfaces only. Due to the variability of paints and finishes it is recommended to test a sample for adhesion.
- Ensure the floor surface is clean from contamination, dust free, and any painted surface is sound.
- No liability is given for damage to painted surfaces as the bond between the paint and the wall is out of our control.
- Make sure edges are applied well. Allow 24 hours to cure before being exposure to moisture or cleaning.
- Avoid exposure to heavy traffic. If edges of graphics begin lifting, replace graphics immediately to avoid the risk of tripping hazard.
- The product meets slip resistance standards when wet however slip resistance is reduced when wet or dirty.

Face Film		Print	'Metamark Digital Vinyl' grey print
Face Film Gauge	Monomeric calendered PVC 100 micron nominal	Weight Type	140 gsm nominal Layflat kraft with PE coating
Tensile Strength	65N/25mm MD / 57N/25mm TD nom	Roll Presentation	
Adhesive Type	Permanent clear solvent-based acrylic	Roll sizes and net weights	760mm x 50m 12kg 1370mm x 50m 22kg 1520mm x 50m 24kg
Weight Adhesion to glass 20 mins	20gsm nominal 14N/25mm nominal 18N/25mm nominal	Durability	
Adhesion to glass 24 hour Perceived tack Application temperature Service temperature	High +10°C to +60°C -30°C to +110°C	Shelf Life External weathering Fire Rating	years years for use not on floors (walls). year under normal floor use. Self Extinguishing
Finishes		Certification	BS 7976-2:2002 cert (Slider 96)
Finishes Available	MG-F MetaGuard 'FloorArt'	Regulations	DIN 51130:2014 – Category R9 <u>See</u> certification report REACH compliant
Release Liner			

Warranty: Metamark (UK) Limited warrants to its customers that graphics produced using Metamark Digital Media will remain in good condition without excessive fading or colour degradation for the specified life time of the ink used, when correctly stored, printed and applied in accordance with procedures outlined in the technical literature. If within the specified years of normal use Metamark DigitalVinyl becomes ineffective for its intended use, then Metamark will provide sufficient material to produce a new replacement marking, and will at its own discretion, contribute an allowance in additional material towards the costs involved in replacing the graphics. In all cases, the converter is held fully responsible for storing, processing and applying the unconverted materials in accordance with Metamark's technical specifications. Metamark (UK) Limited will not be liable for any indirect or consequential loss or damage, and will not provide any allowance against improper usage, application accident, negligence, chemical damage or improper repair. Please Note: The above data is given in good faith to provide an indication of the performance of the product. Purchasers should consider the suitability of each product for its intended use and the purchaser assumes all risks in connection with such use. Seller shall not be liable for damages in excess of the purchase price of the product nor for incidental nor consequential loss.

Metamark (UK) Limited